


SLI Battery For passenger vehicles



Part information

Part No:	0092S40180
Short code:	S4018
Product line:	S4
Technology:	SLI - Starting-Lighting-Ignition*
EAN code:	4047023479990



Technical information

Nominal Voltage:	12 V			
Nominal capacity: (20 hr discharge down to 10.5 V)	C20	40 Ah		
Reserve capacity: (@ 25 A)				
Cold cranking amps: (EN / -18°C U10s ≥ 7.5 V)	330 A			
Group size:	B19H			
JIS type:	-			
Short-time angle of inclination:	55°			
Permanent angle of inclination:	0°			
Dimension:	Length	Width	Ht. w/o terminal	Ht. w terminal
	187 mm	140 mm		227 mm
Total battery weight: (approx., filled battery)	9,74 kg			
Layout: (ETN, DIN 72331)	0			
Terminal: (ETN, DIN 72331)	3			
Base hold down: (ETN, DIN 72331)	B00			
Degassing:	Central			

Technical data

Application:	Conventional		
Service:	Maintenance-free		
Standard charging:	Charging voltage:	14,4 V	
	Charging current:	4 A	
	Charging pattern:	IU	
European standards:	DIN EN 60095-1, -2, -4 Lead-acid starter batteries; DIN EN 50342 Lead-acid starter batteries; DIN 41 773, Charger with IU characteristics		

*SLI (Starting-lighting-ignition): lead-acid starting-lighting-ignition/starter battery